



## **2023 Johnstone Supply Super Truck Rules**

THE RULES AND/OR REGULATIONS SET FORTH HEREIN ARE DESIGNED TO PROVIDE FOR THE ORDERLY CONDUCT OF RACING EVENTS AND TO ESTABLISH MINIMUM ACCEPTABLE REQUIREMENTS FOR SUCH EVENTS. THESE RULES SHALL GOVERN THE CONDITION OF SPEEDWAY EVENTS AND, BY PARTICIPATING IN THESE EVENTS, ALL RACEWAY COMPETITORS ARE DEEMED TO HAVE COMPLIED WITH THESE RULES. NO EXPRESS OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATION OF, OR COMPLIANCE WITH THESE RULES AND REGULATIONS. THEY ARE INTENDED AS A GUIDE FOR THE CONDUCT OF THE SPORT AND IN NO WAY ARE A GUARANTEE AGAINST INJURY OR DEATH TO PARTICIPANTS, SPECTATORS OR OTHERS.

**If it doesn't say you can "you can't"**

### **OVERVIEW**

1. These rules are intended to provide fair and competitive racing for all participants in this division in which the standard is set forth for the Southwest Super Truck Association (SWSTA). SWSTA officials are authorized to determine if an equipment change or addition is an attempt to circumvent these rules or provide an unfair advantage. Officials can disqualify any entry in violation of these rules or an attempt thereof. Decisions will be impartially based on logic, fairness and consistency. If there is a disagreement or dispute regarding the meaning, interpretation or application of these rules, the official's decisions shall prevail.
2. Modification of these rules without the official's consent in any way is considered illegal. Questions and/or concerns regarding the validity of a modification not specified in these rules must be addressed in writing to the SWSTA rules committee. The official's decisions are final and have the right to confiscate illegal components and/or sequester the Super Truck in question at any time. Any driver found to be blatantly utilizing illegal components will be assumed to have competed dishonestly and will forfeit all earned points at all tracks for the current season—NO EXCEPTIONS.
3. Track officials can alter or amend these rules only in agreement with the SWSTA officials in the best interest of safety, cost control, and fair competition. No implied warranty of safety shall result from the publication of, amendments to, or compliance with these rules. The safety of each Super Truck and all equipment is the responsibility of the driver and owner.
4. Association dues are \$75 per year, due by the first race, otherwise you will pay \$10 to race each race. The membership dues register the Super Truck for the season and provides the driver with benefits of association incentives such as tow money for participating in out-of-town Super Truck races, end-of-season points payouts. Race points go to driver.
5. All rookie drivers will start at the rear of the field in both the heat and main event races, for 3 or 4 races, or until the association has determined that the rookie driver is experienced enough to handle various starting positions.
6. Please contact Cliff Evrage, President, at (575) 626-7505 or Art Viramontes, Vice-President, at (575) 639-1397 for rules clarifications.

### **RULES VIOLATIONS**

1. All Super Trucks are subject to inspection randomly at any time. If a violation is found, it must be corrected prior to the following race in order to receive points and payouts for that race. The driver

will start scratch in all races—earning no points or payouts—until the violation is corrected. The inspection officials and track officials reserve the right to disqualify any Super Truck or driver from competition with just cause.

2. Super Trucks must be re-inspected if any changes have been made since the initial inspection (i.e. replacing intake gaskets). Otherwise, there is the assumption of blatant violation of rules if the Super Truck passed the initial inspection but not subsequent inspections. This may result in loss of accrued season points at all SWSTA sanctioned tracks per agreement of SWSTA officials.
3. When in doubt, clarify the rules with the SWSTA president. We support the drivers and want to encourage your full participation so that you can enjoy the benefits of being a member of the SWSTA.

## **FRAME**

1. Four-point main cage within ¼" location. All tubing for the complete cage, front and rear, must be 0.095" x 1.75" tubing.
2. Front post of cage must be positioned 5/8" behind the beginning of the side channel on both sides of a metric GM mid-sized frame, (Monte Carlo, Cutlass, Regal, Grand Prix, etc., can X frame).
3. The rear posts will be 45.5" behind the front posts. These posts are centered upon the side channels and 23" tall.
4. A one-piece hoop fits on them and is the upper door bar and front hoop.
5. The halo is 42" front and rear, above the side channels of the GM frame.
6. The halo is 30.5" center to center, front to rear, and is 50.5" wide centered above frame.
7. The lower door bar is 10" wider than the frame channel on each side and 6" above the channel to the center of the lowest door bar.
8. All frame mounting points must be maintained. This is a spec classification.
9. There must be four (4) door bars on the driver's side and three (3) door bars on the passenger side.
10. If the Super Truck has a passenger seat, the right side must also have four (4) door bars. Any side that has a seat must be plated on the outside of the door bars to prevent intrusion of bumper bars or other objects.
11. The front bumper is at the top of the front stub molded inside the nose piece. External front bumpers or excessive bracing is not allowed.
12. The rear bumper is located at the top of the rear clip in the same manner. The rear bumper should have upper and lower hoops so that the single front bumper will contact in race conditions. The bumper is recommended to be mounted inside the body. Cow catchers are not allowed.
13. Each participant must consult with class officials as to the legality of each frame. This is not a builder's competition; Each frame is the basis of equality.
14. Side nerf bars must have turned-in ends and rounded bolt heads for attachment, centered at the bottom of the lower door bar. Only continuous radius rear side nerf allowed. Rub rails must mount flush with the body, not spaced out from body.

## **SUSPENSION**

1. Suspension mounting points may not be altered (exception: upper "A" arm mounts may be fabricated to accept an aftermarket arm). Any type upper arm is allowed. Suspension points will be inspected.
2. Front spindles, rotors, lower "A" arms, mounts, calipers, steering components and all rear axle trailing arms must be OEM mid-sized metric parts. Direct replacement parts cannot be altered except to add shock mount to lower arm and to ream the ball joint holes to accept the ball joints. May also use 14" sledge tubes and/or heim joints as tie rod adjusters. These will be inspected, and modifications will be subject to disqualification.
3. All ball joints allowed.
4. Wheels must be steel with a 2" back space. Bead locks with dimensions of 15" x 8" width are allowed on both right side tires.

5. Studs of ½" or larger are required.
6. Grooved or excessively thin rotors, drilling or machining is prohibited.
7. A 58" Ford floated hub axle or metric axle is allowed. All axles must be locked with mini or full spool made of steel only. Tolerance of ¾" on width of axle is permitted. Lower trailing arm mount bolts on 9-inch Ford must be FIXED at 2-2.5" inches from axle tube to center of the bolt—no lower. This is based on a 3" tube diameter; larger tubes will be closer. Upper mounts are 10" on the left and right above the mount holes centerline. Pinion angle must be a maximum of 5 degrees. There is a jig for a 58" Ford/metric floater. The mounting points must be within 1" variance of the jig points on top, when placed on the rear-axle.
8. Any suspension bushing can be used with original holes in arms and mounts. Holes may be drilled out to ½".
9. Springs must be mounted in original locations. Only non-metallic spacers allowed.
10. Must have Three (3) operable brakes, proportioning valve front to rear along with a balance bar, and shut-off right front valve only are also permitted.
11. All Super trucks must run disc brakes all around. Only steel rotors and mid-sized metric calipers are permitted. Aluminum or other exotic metals are not allowed.
12. Floater hubs are recommended but not required.
13. Brake fluid recirculators are permitted.
14. Steel brake lines are highly recommended.
15. Sway bars are optional but must be OEM solid steel bar. Mounting methods are optional and may have adjustable ends.
16. One shock per wheel with no external reservoir shocks allowed. Shocks are limited to a \$150 value for a new retail purchase price.
17. Trailing arms must be OEM mid-sized metric length. Aftermarket trailing arms are allowed.

## **DRIVE TRAIN**

1. Any OEM transmission attached to the bellhousing (3-speed Saginaw, Power Glides, etc.). Must have working reverse and at least one working forward gear. Aftermarket transmissions (e.g. Bert, Brinn, Falcons, Tex Racing, Richmond, etc.) are permitted.
2. Any Super Truck with OEM clutch cover must run explosion-proof bellhousing.
3. Light weight flex-plates are prohibited.
4. Single steel drive shaft must be painted white with a 2" x 3/16" hoop (or equivalent), 6" to 15" behind front "U" joint.

## **TIRES**

1. Tires permitted are the American Racer KK704 only.

## **ENGINES**

All engine packages must utilize a 7,000 RPM chip.

1. Chevy and Ford engines, 360 cubic inches; Dodge 370 cubic inch maximum, 1% error, with 9.5:1 compression ratio (5% tolerance). Engine block must be OEM production with original specifications. Any exhaust header with any muffler permitted. Mufflers or track approved baffles are required.
2. Flat top or dished pistons only. No part of the piston may protrude above the deck surface.
3. Titanium engine or truck pans are not allowed.
4. Any roller rocker arm is permitted.
5. Flat tappet cams only, hydraulic or solid lifters. Maximum lift is 0.540" intake and 0.560" on exhaust, measured at zero lash on valve retainer. Lifter must be able to be removed from the top of the lifter bore.
6. Engine must be 93" or more from center line of rear axle to rear of engine block.

7. Aftermarket cast iron heads are permitted with stock valve angles. Ford may use World Products casting.
8. Cold air box is optional and must pick up air at the base of the windshield. Forward facing scoops or Ram Air are not allowed.
9. Only 2-barrel or 4-barrel carburetors permitted, no other exotic type or Predator.
10. Carburetor base dimensions must be no more than 7" above top of block measured with a straight edge across the spacer down to top of the block at rear manifold.
11. Gasoline and approved race fuel only. Additives, nitrous oxide or other oxygenating substances are not allowed. A 16-gallon fuel cell in a steel box mounted behind the rear axle is required. (2) 2" straps must encompass the entire fuel cell. The bottom of the fuel cell must be level with the top of rear frame horns.
12. Glass and plastic fuel lifters are prohibited.
13. Mechanical block mounted fuel pumps are required. Mechanical belt-driven fuel pump is allowed.
14. Radiator must be mounted in front of engine with an overflow 2-quart minimum canister.
15. Battery must be mounted behind the driver within the frame in an approved battery mount.
16. Any electronic or mechanical traction control devices are prohibited.
17. Any approved distributor-type ignition is permitted. Crank triggers, magnetos and timing-controlled ignition systems are prohibited.
18. Must start under own power. Any truck requiring a push start will be placed in scratch position.

#### **Rules for the LS 5.3 engine:**

1. The engine will be a cast iron port head style, with the size being 5.3 liters.
2. OEM crankshaft, rods, pistons, heads, 1.7 ratio rocker arms, lifters, cam chain required.
3. The camshaft will be the original cam or may be replaced with the CT525 camshaft only.
4. The intake manifold will be the Holley 300-132 with 1-inch adapter.
5. Holley 4412 will be required, with choke horn.
6. Must use the MSD ignition box.
7. Aftermarket parts that may be used: pan, water pump, pulleys, headers, oil filter adapter.
8. Winters crank flange adapter may be used to convert the bolt pattern to standard drive pattern.
9. Must add 80 pounds at engine plate if utilizing an aluminum block.
10. Mechanically driven fuel pump recommended. Electric pump with appropriate oil psi shut-off and roll-over shut-off allowed.

#### **BODIES**

1. Bodies must have truck molded nose, tail, roof and roof posts; All others must be made of aluminum. Home-made parts of the above mentioned are prohibited.
2. A 6" spoiler with no forward supports is permitted but must be no wider than rear deck.
3. Minimum weight of Super Truck with driver inside is always 2,750 pounds with a maximum of 3,250 pounds. Extra roll cage elements and other driver protection are recommended for reaching weight requirements.
4. Driver's compartment is open side to side or closed.
5. Ballast inside driver's compartment is prohibited.
6. All ballasts will have two (2) 5" bolts attached to the frame or equivalent (subject to inspection approval) painted white with Super Truck number on it.
7. No sail panels on and/or behind roof. No wicker bills.

#### **SAFETY**

1. Five-point seat belt system, is required. System must be properly mounted to main cage using 7/16" grade 8 bolts to secure belts.
2. Snell helmet SA2005 or newer, fire suit, gloves, neck brace (or HANS device system, highly recommended) and driving shoes required.

3. Fuel turn-over valve or vented safety cap required.
4. Professionally built aluminum racing seat securely and safely bolted to the cage required.
5. Holes are not allowed in driver's compartment except for drain hole in floor. One 2" hole in each rear corner of the floor is permitted.
6. A 1" ribbon-type net permanently mounted on the bottom with an approved quick release at the top front required. Net must cover window opening. Arm restraints are not a substitute. Net must be positioned to enter the racing surface and remain in place for the duration of the race/event.
7. It is recommended to incorporate a brake pressure activated ignition kill switch which would interrupt the ignition in the event of a stuck throttle to allow the driver in maintaining control and safely stop the truck.
8. All roll cage tubing in reach of driver must be padded.
9. All personal safety equipment must be within expiration dates. Holes, tears and excessive fluid stains are not allowed. Material will burn when fueled by an added combustible substance such as oil. Occasionally wash your gear according to factory recommendations.

## **NUMBERS**

1. Only numbers registered with the SWSTA will receive points and monies.
2. Registered numbers from the previous season have the option to retain same number.
3. All Super Trucks must have a clearly visible 4" number on the left rear bumper.
4. No duplication of numbers. Out-of-area Super Trucks competing once or twice may run a duplicate number accompanied by an "X" or other letter.

## **TRANSPONDERS**

Transponders are mounted on the rear next to the fuel cell. The plate is attached to the front of the fuel cell support brace with the transponder pouch opening facing the rear. The transponder support and pouch are mounted with the closest side 5.5" behind the shock mounting X member will be checked with a gauge. This will determine positions when crossing the finish line.

**These mufflers must be run on all divisions except Legends and Claimers. Valid part numbers: 112530, 112535, 113035 and 14272735-78.**

# Sanction Approved Mufflers

Temporary non-high temperature paint

LENGTH	WEIGHT	INLET DIA.	OUTLET DIA.	BODY DIA.	SANCTION APPROVED	PART #	PRICE
11"	2.35#	3"	3"	3 1/2"	-----	112530	38.95
11"	2.84#	3 1/2"	3 1/2"	4 3/8"	-----	112535	38.95
11"	2.90#	3 1/2"	3 1/2"	4 3/8"	-----	113035	38.95
14"	4#	3 1/2"	3 1/2"	4 1/2"	ASCS - W.O.O	14272735-78	69.95



Copyright © 2020-2021 Vado Speedway Park. All rights reserved.